

A blurred, winding road through a forest at sunrise or sunset. The road curves to the right, with a white line marking the edge. The background shows a dense forest of evergreen trees, and the sun is low on the horizon, creating a warm, golden glow. The text "Exploration Strategy Future" is overlaid in white, centered on the road.

Exploration  
Strategy  
Future





DK518

HIGH-PERFORMANCE  
TYRE SERIES



DK718

HIGH-PERFORMANCE  
TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
205/40ZR17	84	WXL	7 1/2J	212	596	500	1102	340	49
235/40ZR18	95	WXL	8 1/2J	241	645	690	1518	340	49

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
225/45ZR19	92	W	7.5J	225	685	630	1389	300	44
235/50R19	99	V	7 1/2J	245	719	775	1709	300	44
235/55R19	105	VXL	7 1/2J	245	741	925	2039	340	49
245/50R20	102	V	7.5J	253	754	850	1874	300	44
245/55R19	103	V	7.5J	253	753	875	1929	300	44
245/45ZR20 XL	103	W	8J	243	728	875	1929	340	49
245/40ZR19	98	WXL	8 1/2J	248	679	750	1653	340	49
255/40ZR19	100	WXL	9J	260	687	800	1764	340	49
255/50R19 XL	107	V	8J	265	739	975	2149	340	49
255/55R19 XL	111	V	8J	265	763	1090	2403	340	49
275/45ZR20 XL	110	W	9J	273	756	1060	2337	340	49
275/45ZR21 XL	110	W	9J	273	781	1060	2337	340	49



DK728

HIGH-PERFORMANCE  
TYRE SERIES



DK798

HIGH-PERFORMANCE  
TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
195/50R16	84	V	6.0J	201	602	500	1102	300	44
205/45R16	83	W	7J	206	590	487	1074	300	44
205/50R16	87	V	6 1/2J	214	612	545	1201	300	44
205/55R16	91	V	6.5J	214	632	615	1356	300	44
215/50ZR17	91	W	7J	226	648	615	1360	300	44
215/55ZR17	94	W	7J	226	668	670	1477	300	44
215/55ZR17	98	WXL	7J	226	668	750	1653	340	50
235/60R16	100	V	7J	240	688	800	1764	300	44
235/60R16	104	VXL	7J	240	688	900	1984	340	50

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
205/45ZR17	84	W	7J	206	616	500	1102	300	44
215/45ZR17 XL	91	WXL	7J	213	626	615	1356	340	50
225/40ZR18	92	WXL	8J	230	637	630	1389	340	50
225/45ZR17	91	W	7 1/2J	225	634	615	1356	300	44
225/45ZR18	91	W	7.5J	225	659	615	1356	300	44
225/50ZR17	94	W	7J	233	658	670	1477	300	44
225/50R18	95	V	7J	233	683	690	1521	300	44
225/55ZR17	97	W	7J	233	680	730	1609	300	44
225/55R18	98	V	7J	233	705	750	1653	300	44
235/45ZR17	94	W	8J	236	644	670	1477	300	44
235/45ZR18	94	W	8J	236	669	670	1477	300	44
235/50ZR17	96	W	7 1/2J	245	668	710	1565	300	44
235/50ZR18	97	W	7 1/2J	245	693	730	1609	300	44
245/50R18	100	V	7 1/2J	253	703	800	1764	300	44
245/45ZR17	95	W	8J	243	652	690	1521	300	44
245/45ZR18	96	W	8J	243	677	710	1565	300	44
245/45ZR19	98	W	8J	243	703	750	1655	300	44
245/40ZR18	93	W	8.5J	248	653	650	1433	300	44
255/45ZR18 XL	103	W	8.5J	255	687	875	1929	340	49
255/55R18	109	VXL	8J	265	737	1030	2271	340	49





## DK106

HIGH-PERFORMANCE  
TYRE SERIES



## DK316

HIGH-PERFORMANCE  
TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
155/80R13	79	S	4.50B	157	578	437	963	250	36

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
155/65R14	75	T	4 1/2J	157	558	387	853	300	44
165/65R15	81	H	5J	170	595	462	1019	280	41
165/70R13XL	83	S	5.00B	170	562	487	1074	290	42
175/65R15	84	H	5J	177	609	500	1102	300	44
175/70R13XL	86	S	5.00B	177	576	530	1168	290	42



## DK207

### HIGH-PERFORMANCE TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
155/80R12	77	S	4.50B	157	553	412	908	260	38

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
155R12LT	8PR 88/86	Q	4.50B	157	553	560/530	1235/1168	450	65
155R13LT	8PR 90/88	Q	4.50B	157	578	600/560	1323/1235	450	65
165R13LT	8PR 94/93	Q	4.50B	165	594	670/650	1477/1433	450	65
175R13LT	8PR 97/95	Q	5.00B	177	610	730/690	1609/1521	450	65



## DK108

### HIGH-PERFORMANCE TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
145/70R12	69	T	4.50B	150	509	325	716	270	39
155/65R13	73	T	4.50B	157	532	365	805	300	44
155/70R13	75	T	4.50B	157	548	387	853	300	44
165/70R13XL	83	S	5.00B	170	562	487	1074	290	42





DK308

HIGH-PERFORMANCE  
TYRE SERIES



DK318

HIGH-PERFORMANCE  
TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
205/70R14	95	T	6J	209	644	690	1521	280	41

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
165/65R13	77	S	5.00B	170	544	412	908	280	41
165/70R14	85	T	5J	170	588	515	1135	290	42
175/70R13XL	86	S	5.00B	177	576	530	1168	290	42
185/70R13	86	T	5.50B	189	590	530	1168	270	39
185/70R14	88	T	5.5J	189	616	560	1235	280	41
195/60R14	86	H	6J	201	590	530	1168	280	41
195/70R14	91	T	6J	201	630	615	1356	280	41



DK558

HIGH-PERFORMANCE TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
165/60R14	75	H	5J	170	554	387	853	300	44
165/65R14	79	T	5J	170	570	437	963	270	39
165/80R13	83	H	4.50B	165	594	487	1074	300	44
175/60R14	79	H	5J	177	566	437	963	300	44
175/60R13	77	H	5.00B	177	540	412	908	300	44
175/65R14	82	H	5J	177	584	475	1047	290	42
175/70R14	84	T	5J	177	602	500	1102	300	44
185/60R14	82	H	5 1/2J	189	578	475	1047	280	41
185/55R15	82	H	6J	194	585	475	1047	300	44
185/60R15	84	H	5 1/2J	189	603	500	1100	300	44
185/65R15	88	H	5 1/2J	189	621	560	1235	300	44
185/80R14	91	T	5J	184	652	615	1355	300	44
195/50R15	82	V	6J	201	577	475	1047	300	44
195/55R15	85	V	6J	201	595	515	1135	280	41
195/55R16	87	V	6J	201	620	545	1201	300	44
195/60R15	88	H	6J	201	615	560	1232	300	44
195/60R14	86	H	6J	201	590	530	1168	280	41
195/60R16	89	H	6J	201	640	580	1279	300	44
195/65R15	91	H	6J	201	635	615	1353	300	44
205/65R15	94	H	6J	209	647	670	1477	300	44
205/65R16	95	H	6J	209	672	690	1521	300	44
205/55R16	91	V	6.5J	214	632	615	1356	300	44
205/60R16	92	H	6J	209	652	630	1389	300	44
205/60R15	91	H	6J	209	627	615	1356	300	44
205/60R14	88	H	6J	209	602	560	1234	280	41
215/60R16	93	V							
215/60R15	94	H	6 1/2J	221	639	670	1477	300	44
215/65R15	96	H	6 1/2J	221	661	710	1565	300	44
215/65R16	98	H	6 1 2J	221	686	750	1653	300	44
215/55R16	93	V	7J	226	642	650	1433	300	44
225/55R16	95	V	7J	233	654	690	1521	300	44
225/60R16	98	V	6 1/2J	228	676	750	1653	300	44
225/60R16	102	VXL	6 1/2J	228	676	850	1874	340	49

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
175/70R14LT	8PR 95/93	S	5J	177	602	690/650	1521/1433	375	54



DK168

HIGH-PERFORMANCE TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
135/70R12	65	Q	4.00B	138	495	290	639	250	36





DK298

HIGH-PERFORMANCE  
TYRE SERIES



DK109

HIGH-PERFORMANCE  
TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
185/60R14	82	H	5 1/2J	189	578	475	1047	280	41
185/65R14	86	H	5 1/2J	189	596	530	1168	280	41

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
155/70R12	73	T	4.50B	157	523	365	805	270	39
155/80R12	77	S	4.50B	157	553	412	908	260	38
155/80R13	79	S	4.50B	157	578	437	963	250	36
165/70R12	77	T	5.00B	170	537	412	908	270	39





# DK169

## HIGH-PERFORMANCE TYRE SERIES



# DK205

## LIGHT TRUCKS TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
145/70R12	69	T	4.50B	150	509	325	716	270	39

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
500R12LT	10PR 87/85	P	3 1/2J	139	565	545/515	1201/1135	550	80
550R12LT	10PR 92/90	M	4.00B	160	595	630/600	1389/1323	550	73
LT550R13	12PR 97/95	P	4.00B	168	625	730/600	1609/1521	625	91





DK218

LIGHT TRUCKS TYRE SERIES



DK228

LIGHT TRUCKS TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
185R14LT	8PR 102/100	S	5.5J	189	652	850/800	1874/1764	450	65
185R15LT	8PR 103/102S	S	5.5J	189	677	875/850	1929/1874	450	65
195R14LT	8PR 105/103	S	5 1/2J	196	668	925/875	2040/1930	450	65
205R14LT	8PR 107/105	R	6J	208	684	975/925	2149/2039	450	65

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
215R14LT	8PR 110/108	R	6J	216	700	1060/1000	2335/2205	450	65





DK868

LIGHT TRUCKS TYRE SERIES



DK206

LIGHT TRUCKS TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
165R14LT	8PR 97/95	R	4.5J	167	622	730/690	1610/1521	450	65
165/70R14LT	8PR 90/87	R	5J	170	588	600/540	1323/1202	450	65
175/75R14LT	8PR 94/91	R	5J	177	618	670/615	1477/1356	450	65
175R14LT	8PR 99/98	R	5J	178	636	775/750	1710/1655	450	65
205/70R15LT	8PR 106/104S	S	6J	209	669	950/900	2095/1985	450	65
215/70R15LT	8PR 106/104S	S	6.5J	221	683	950/900	2095/1985	375	55

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
195R15LT	8PR 106/104R	R	5 1/2J	196	693	950/900	2095/1985	450	65





## DK208

### ALL SEASON LIGHT TRUCKS TYRE SERIES



## DK768

### ALL SEASON LIGHT TRUCKS TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
205R16LT	110/108	Q	6J	208	734	1060/1000	2339/2206	450	65
650R15LT	10PR 106/101	N	5.50F	185	730	950/825	2095/1820	560	81
650R16LT	10PR 107/102	N	5.50F	185	750	975/850	2150/1874	560	81
700R15LT	10PR 109/105	L	5.50F	200	775	1090/975	2403/2150	560	81
700R16LT	12PR 115/110	L	5.50F	200	775	1215/1060	2680/2335	670	97
750R16LT	12PR 120/116	L	6.00G	215	805	1400/1250	3086/2756	670	97

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
185/65R15 LT	94/91 8PR	R	5.5J	189	621	670/615	1477/1356	450	65
185/75R16LT	8PR104/102R	R	5.0J	184	684	900/850	1985/1875	475	69
195/70R15LT	8PR 104/102R	R	6J	201	655	900/850	1985/1875	450	65
195/75R16LT	8PR 107/105R	R	5 1/2J	196	698	975/925	2150/2040	475	69
215/75R16LT	10PR 112/109	Q	6J	216	728	1120/1030	2469/2271	550	80
225/70R15LT	8PR 112/110R	R	6 1/2J	228	697	1120/1060	2470/2335	450	65



# DK365

## SUV COMFORT TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
225/75R16SUV	104	T	6.0J	223	744	900	1985	300	44
215/70R16SUV	100	H	6.5J	221	708	800	1764	300	44
225/70R16SUV	103	H	6.5J	228	722	875	1929	300	44
235/70R16SUV	106	H	7J	240	736	950	2094	300	44
245/70R16SUV	107	H	7J	248	750	975	2149	300	44
265/70R16SUV	112	H	8J	272	778	1120	2469	300	44
265/70R17SUV	115	H	8J	272	804	1215	2679	300	44
215/60R17SUV	96	V							
225/60R17SUV	99	H	6 1/2J	228	702	775	1709	300	44
225/60ZR18SUV	100	H	6.5J	228	727	800	1764	300	44
235/60ZR18SUV	103	H	7J	240	739	875	1929	300	44
265/60ZR18SUV	110	H	8J	272	775	1060	2337	300	44
285/60R18SUV	116	H	8.5J	292	799	1250	2756	300	44
225/65R17SUV	102	H	6.5J	228	724	850	1874	300	44
235/65R17SUV	104	H	7J	240	738	900	1984	300	44
245/65R17SUV	107	H	7J	248	750	975	2149	300	44
265/65R17SUV	112	H	8J	272	776	1120	2469	300	44
235/55R17SUV	99	V	7.5J	245	690	775	1709	300	44
285/65R17SUV	116	H	8 1/2J	292	802	1250	2756	300	44
215/55R18SUV	95	H	7J	226	693	690	1521	300	44
235/55R18SUV	100	H	7 1/2J	245	715	800	1764	300	44





DK219

LIGHT TRUCKS TYRE SERIES



DK309 A/T

SUV A/T ALL-ROAD-CONDITION  
TIRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
600R13LT	10PR 98/94	P	4.50B	170	655	750/670	1650/1477	530	77
600R14LT	10PR 100/96	P	4 1/2J	170	680	800/710	1764/1566	530	77
600R15LT	10PR 101/97	N	4.50E	170	705	825/730	1820/1609	560	81
600R16LT	10PR 102/98	N	4.50E	170	730	850/750	1874/1654	560	81

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
215/75R15LT	6PR 100/97	S	6J	216	703	800/730	1765/1610	350	50
225/75R15LT	6PR 110/108	S	6J	223	719	1060/1000	2335/2205	375	54
235/75R15LT	6PR 104/101	S	6.5J	235	733	900/825	1985/1820	350	50
235/70R16LT	6PR 104/101	R	7J	240	736	900/825	1985/1820	350	50
245/70R16LT	6PR 111/109	R	7J	248	750	1090/1030	2405/2270	375	54



## DK 788 A/T

SUV A/T ALL-ROAD-CONDITION  
TIRE SERIES



## DK301 A/T

SUV A/T ALL-ROAD-CONDITION  
TIRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
31*10.5R15LT	6PR 109Q	Q	8 1/2J	268	775	1030	2270	350	51
225/75R16LT	8PR 110/107	R	6J	223	744	1060/975	2335/2150	450	65
225/75R16LT	10PR 115/112	R	6J	223	744	1215/1120	2680/2470	550	80
245/75R16LT	10PR 120/116	R	7J	248	774	1380/1260	3042/2778	550	80
235/85R16LT	10PR 120/116	R	6 1/2J	235	806	1380/1260	3042/2778	550	80
265/75R16LT	10PR 123/120	R	7 1/2J	267	804	1550/1400	3415/3085	550	80
255/75R17	115	T	7J	255	814	1215	2679	300	44

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
255/70R15LT	8PR 113/110S	S	7.5J	260	739	1150/1060	2535/2335	450	65





DK778

WEAR RESISTING  
TYRE SERIES



DK868

TRAILER TYRE SERIES



SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
175/70R14TAXI	84	T	5J	177	602	500	1102	300	44
185/60R14TAXI	82	H	5.5J	189	578	475	1047	300	44
195/60R14TAXI	86	H	6J	201	590	530	1168	300	44
195/65R15TAXI	91	H	6J	201	635	615	1356	300	44
185/65R15TAXI	88	H	5 1/2J	189	621	560	1235	300	44
185/60R15TAXI	84	H	5 1/2J	189	603	500	1102	300	44
195/60R15TAXI	88	H	6J	201	615	560	1235	300	44
205/60R15TAXI	91	H	6J	209	627	615	1356	300	44
205/65R15TAXI	94	H	6J	209	647	670	1477	300	44
205/55R16TAXI	91	V	6.5J	214	632	615	1356	300	44
215/60R16TAXI	95	V	6 1/2J	221	664	690	1521	300	44

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
ST175/80R13	6PR	Q	5.00JB	177	610	615	1360	350	50
ST185/80R13	6PR	Q	5.00JB	184	626	670	1480	350	50
ST205/75R14	6PR	Q	5.5J	203	664	800/710	1760/1570	350	50
ST205/75R14	8PR 105	Q	5 1/2J	203	664	925/825	2039/1819	450	65
ST205/75R15	6PR	Q	5.5J	203	689	825/730	1820/1610	350	50
ST205/75R15	8PR 107	Q	5 1/2J	203	689	975/850	2149/1870	450	65
ST225/75R15	8PR 113	Q	6J	223	719	1150/1000	2540/2205	450	65
ST235/80R16	10PR 123	Q	6 1/2J	235	782	1600/1360	3527/2998	550	80
ST235/85R16	10PR 125/121	PR	6.5J	235	806	1650/1450	3640/3200	550	80



# DK306

## SUV COMFORT TYRE SERIES

SIZE	LOAD INDEX	SPEED INDEX	STANDARD RIM	SECTION WIDTH mm	OUTER DIAMETER mm	MAX.LOAD		MAX.PRESSURE	
						kg	lbs	kpa	psi
LT225/75R15	8PR 108/104	Q	6J	223	719	1000/900	2205/1985	450	65
LT235/75R15	10PR 116/113	Q	6 1/2J	235	733	1250/1150	2755/2535	550	80
P215/75R15SUV	100	S	6J	216	703	800	1764	260	38
P225/75R15SUV	102	S	6J	223	719	850	1874	260	38
P235/75R15SUV	105	S	6 1/2J	235	733	925	2039	260	38